



MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® RG 179 U - Mil. C 17 Standard

1x0,05 mm² - Coaxial Cable 75 Ω



CATEGORY Coaxial cable 75 Ω (See Video Catalogue)
APPLICATIONS mini-coax video signals

- A:** Transparent Fluorinated Ethylene Propylene (**FEP Teflon**) Sheath. Flame Retardant Self-Extinguishing (IEC 60332-1-2) , Halogen Free, UV, water, Chemical, solvents and Oil Resistant. Specifically designed for high or low temperature also for Outdoor Application.
Outer Diam. Ø 2,54 (±0,10) mm.
- B:** Shielding in O.F.C. **silver plated copper** braid covering 95%.
- C:** Core Insulation with Transparent Fluorinated Ethylene Propylene (**FEP Teflon**) – Diam. Ø 1,58 (±0,20) mm.
- D:** Stranded formation in **silver plated copper** formation 7x0,10 mm. Nom. Cross section 1x0,05 mm².

MARKING Cable not marked
CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PVC, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	830 Ω/Km
Capacity Core/Shield	64 pF/mt
Velocity of Propagation	69%
Impedance	75 Ω
Operative Temperature	-60/+200°C

Attenuation db/10 mt

50 MHz	2,80
100 MHz	3,30
400 MHz	5,30
700 MHz	6,50
1000 MHz	7,90

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
	X	Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			